MILBANK[®] ENERGYAT WORK

U6193-YL-QG-AMS



Catalog Number	U6193-YL-QG-AMS
Marketing Product Description	5 Terminal Ringless 1.25 In Hub Quadplex Ground Lever Bypass Ameren
UPC	784572721845
Length (IN)	4.84
Width (IN)	10
Height (IN)	18.5
Brand Name	Milbank
Туре	Ringless Meter Socket
Special Features	Ameren Energy
Application	Meter Socket
Standard	UL Listed;Type 3R
Voltage Rating	600 Volts Alternating Current
Amperage Rating	125 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	4.84L x 10W x 18.5H
Number Of Cutouts	0
Cutout Size	No Main Breaker
Cable Entry	Overhead or Underground
Terminal	Lay in
Insulation	Glass Polyester
Mounting	Surface Mount

Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	5 Terminal
Bypass Type	Lever Bypass
Number of Meter Positions	1 Position
Equipment Ground	Quadplex Ground
Hub Opening	1 1/4 Inch Hub with One Way Screws
Load Side Wire Range	6 AWG - 350 kcmil
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.