



MILBANK
ENERGY AT WORK

U2853-X-KK-K1-PED-CECHA



Catalog Number	U2853-X-KK-K1-PED-CECHA	Terminal	Single Mechanical
Marketing Product Description	4 Terminal Ringless Large Closing Plate Horn Bypass 3 Position 3-125 Ampere Main Breaker Provision Single Connector 6-350kcmil Pedestal Mount Provision Vertical Commonwealth Edison Chicago Housing Authority	Insulation	Glass Polyester
UPC	784572726765	Mounting	Surface Mount
Length (IN)	4.813	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Width (IN)	18	Jaw Quantity	4 Terminal
Height (IN)	37	Bypass Type	Horn Bypass
Brand Name	Milbank	Number of Meter Positions	3 Positions
Type	Ringless Meter Socket	Equipment Ground	Ground Lug
Application	Meter Socket With Main	Hub Opening	Large Closing Plate
Standard	UL Listed;Type 3R	Line Side Wire Range	6 AWG - 350 kcmil
Voltage Rating	Up to 240 Volts Alternating Current	Number Of Receptacles	0
Amperage Rating	125 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	4.813L x 18W x 37H		
Number Of Cutouts	3		
Cutout Size	Breaker Provision		
Cable Entry	Overhead or Underground		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.