



MILBANK
ENERGY AT WORK

U5894-X-2/200-K3L-5T9-MLK



Catalog Number	U5894-X-2/200-K3L-5T9-MLK	Terminal	Single Mechanical
Marketing Product Description	5 Terminal Ringless Large Closing Plate Lever Bypass 2-200 Ampere Breaker 12 Branch Circuit Main Lug Kit Single 4-600kcmil Connector Kit	Insulation	Glass Polyester
UPC	784572748507	Mounting	Surface Mount
Length (IN)	5.938	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Width (IN)	29.5	Jaw Quantity	5 Terminal
Height (IN)	35	Bypass Type	Lever Bypass
Brand Name	Milbank	Number of Meter Positions	1 Position
Type	Ringless Meter Socket	Equipment Ground	3 Barrel Ground Lug
Application	Meter Socket With Main And Load Center	Hub Opening	Large Closing Plate
Standard	UL Listed;Type 3R	Line Side Wire Range	6 AWG - 350 kcmil
Voltage Rating	Up to 240 Volts Alternating Current	Load Side Wire Range	1 AWG - 300 kcmil
Amperage Rating	320 Continuous Ampere	Number Of Receptacles	0
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	5.938L x 29.5W x 35H		
Number Of Cutouts	2		
Cutout Size	Two 200 Ampere Main Breakers		
Cable Entry	Overhead and Underground and Side Wireway		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.