



MILBANK
ENERGY AT WORK

UAP6094-O



Catalog Number	UAP6094-O	NEMA Rating	Type 3R
Marketing Product Description	Aluminum Painted Shell 16 Position Per Phase Bar 500 Kcmil	Hinge Type	Lift Off Hinges
UPC	784572749733	Top	Plain Top
Length (IN)	16	Door	Hinged Cover
Width (IN)	25.625	Latch	Padlocking Handle with 3 Point Latch Assembly
Height (IN)	43	Support	Body Stiffeners
Weight (LB)	105		
Brand Name	Milbank		
Type	Hinge Cover		
Special Features	3000 Ampere; Three Phase Four Wire; Penta Bolt; 10,000 Short Circuit Current Rating		
Application	Terminate Conductors		
Standard	UL Listed		
Number Of Outlet	0		
Material	Aluminum		
Size	16L x 25.625W x 43H		
Color	ANSI 61 Gray		
Insulation	Stand Off's		
Construction	Welded		
Cable Entry	No Knockouts		
Mounting	Pad Mount or Wall Mount		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.