



MILBANK
ENERGY AT WORK

U6266-XTL-200-HSP



| | | | |
|-------------------------------|--|---------------------------|--|
| Catalog Number | U6266-XTL-200-HSP | Mounting | Surface Mount |
| Marketing Product Description | 4 Terminal Ringless 2 Small Closing Plates 1-200 Ampere Main Breaker 8 Branch Circuit Stainless Steel Hasp | Enclosure | G90 Galvanized Steel with Powder Coat Finish |
| UPC | 784572761032 | Jaw Quantity | 4 Terminal |
| Length (IN) | 4.5 | Bypass Type | No Bypass |
| Width (IN) | 14.125 | Number of Meter Positions | 1 Position |
| Height (IN) | 30 | Equipment Ground | Ground Bar |
| Brand Name | Milbank | Hub Opening | Small Closing Plate |
| Type | Ringless Meter Socket | Line Side Wire Range | 6 AWG - 350 kcmil |
| Application | Meter Socket With Main | Load Side Wire Range | 1 AWG - 300 kcmil |
| Standard | UL Listed;Type 3R | Number Branch Circuits | 8 |
| Voltage Rating | Up to 240 Volts Alternating Current | Number Of Receptacles | 0 |
| Amperage Rating | 200 Continuous Ampere | | |
| Phase | 1 Phase | | |
| Frequency Rating | 60 Hertz | | |
| Size | 4.5L x 14.125W x 30H | | |
| Number Of Cutouts | 1 | | |
| Cutout Size | One 200 Ampere Main Breaker | | |
| Cable Entry | Overhead or Underground | | |
| Terminal | Single Mechanical | | |
| Insulation | Glass Polyester | | |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.